



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- 10 year warranty
- maintenance-free shaft sealing with self-lubricating EPDM lip gasket, replaceable under pressure up to DN 80
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- flange connection
- with sidewise drain valve, rotatable hose connection element G 3/4
- spindle thread not in contact with medium
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- DVGW approval up to DN 80
- WRAS approval
- KIWA approval up to DN 100
- VA approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213 / DIN EN 558-1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	bolt holes	A1	D1 (mm)	D2 (mm)	D3 (mm)	D4 (mm)	H1 (mm)	L1 (mm)	S1 (mm)	Zeta	cv (m³/h)	Weight (kg)
1350202500	25	4	G 1/4	70	115	65	25	149	160	13	1	24.2	2.86
1350203200	32	4	G 3/8	70	140	76	32	176	180	15	1.2	37.7	4.20
1350204000	40	4	G 3/8	70	150	84	40	180	200	15	1.3	55.4	5.05
1350205000	50	4	G 3/8	90	165	99	50	221	230	17	0.8	112.5	6.56
1350206500	65	4	G 3/8	90	185	118	65	294	290	17	1.6	132.6	9.88
1350208000	80	8	G 3/8	120	200	132	80	327	310	19	1.4	216.3	12.21
1350210000	100	8	G 3/8	120	220	158	100	302	350	21	2.7	240	19.33
1350212500	125	8	G 3/8	225	250	188	125	488	400	20	3.7	320	35.52
1350215000	150	8	G 3/8	225	285	212	150	295	480	18	3.8	460	51.00

Accessories

- gunmetal sampling valve, figure 187 00
- backing ring for stub flange, figure 410 00
- stub flange, figure 425 00
- extension element for drain valve, figure J6109 473 00
- threaded flange, figure 426 00
- gasket, figure 428 00
- hexagonal bolt and nut, figure 429 M

Spare parts

- drain valve made of gunmetal/plastic, figure J7109 173 00
- handwheel set, figure 999 00
- EPDM seat gasket, figure B9100 173 08
- WESER shut off bonnet with extra long shaft, figure E0109 135 02
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- handwheel, figure G0100
- Installation sleeve for replacement of spindle seal, figure M9100 173 00
- threaded plug , figure J8101 173 00