



Product Features

- thermostatic balancing valve for hydraulic balancing of very short circulation circuits from $kv\text{-min} \geq 0.05$
- for hydraulic balancing of hot water return systems (PWH-C), supports thermal disinfection
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- PTFE seat gasket
- maintenance-free EPDM spindle seal
- thermostatic balancing unit
- plastic shaft can be shortened
- can be extended with optional extension kit
- press connection for Viega SANPRESS SST pipe and PROFIPRESS copper pipe
- chrome-plated cap with allen socket for 6 mm allen key under purple identification plate
- free from dead spots
- with isolating, balancing and pre-setting function

Standards and Approvals

- DVGW approval
- ÖVGW approval
- SVGW approval
- WRAS approval
- for systems according to DVGW worksheet W 551 / W 553 / DIN 1988-300
- according to accepted materials list from German environmental agency
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- max. installation depth 110 mm
- control range 56 °C - 58 °C
- pressure rating PN 16
- max. operating temperature 90 °C

Part no.	DN	A1 (mm)	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	L1 (mm)	SW1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	cv (m ³ /h)	kg
5440201500	15	15	38.5	70	110	35	45	23.5	134	19	22	43.5	46.5	90	0.4	0.77

Accessories

- insulation shell for UP-PLUS and ETA-THERM valves, figure 471 14
- hexagon socket key, size 19, figure B5120 599 00
- UP-PLUS extension set, figure 599 00

Spare parts

- Operating cover for ETA-THERM thermostatic balancing valve, figure 591 01 015
- Balancing bonnet 56-58°C for ETA-THERM thermostatic balancing valve, figure E0109 540 00
- control spindle for flush-mounted valves UP-PLUS, figure P0100 560 00