



Product Features

- pre-assembled
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- suitable for quick and easy installation in the frost-free areas
- inner top part for quick opening operation (two turns)
- high discharge capacity of 40 l / min (1 bar)
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- cone with internal CV spring
- integrated CV and tube aerator as a security combination HD
- inlet male pipe thread
- free from dead spots
- incl. hose coupling for common connection systems
- matt chrome-plated handle with over-twist protection
- fitting is not frost-proof!

Standards and Approvals

- DVGW approval
- according to accepted materials list from German environmental agency

Technical data

- pressure rating PN 16
- max. operating temperature 65 °C

Part no.	DN	A1	A2	H1 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	T1 (mm)	T2 (mm)	flow at 0.05 MPa (l/s)	flow at 0.1 MPa (l/s)	flow at 0.15 MPa (l/s)	Weight (kg)
5790901500	15	R 1/2	G 3/4	71.5	148	26	122	61.5	114	100	0.46	0.67	0.82	0.77

Accessories

- FROSTI® socket key operated head part with socket key, figure 578 00 001
- FROSTI® lockable handle, figure 578 00 003
- FROSTI® lockable handle, for uniform key, figure 578 02 003

Spare parts

- FROSTI® socket key, figure 578 00 004