




### Product Features

- easily replaceable double mesh made of stainless steel
- female pipe thread
- for any installation position



### Technical data

- pressure rating PN 16
- max. operating temperature 200 °C
- mesh width outer supporting sieve 0.6 mm
- mesh width inner screen 0.3 mm

| Part no.   | DN | A1       | H1<br>(mm) | L1<br>(mm) | SW1<br>(mm) | T1<br>(mm) | Zeta | cv<br>(m³/h) | Weight<br>(kg) |
|------------|----|----------|------------|------------|-------------|------------|------|--------------|----------------|
| 6020001500 | 15 | Rp 1/2   | 40         | 65         | 22          | 12         | 3.8  | 4.6          | 0.23           |
| 6020002000 | 20 | Rp 3/4   | 50         | 75         | 24          | 14         | 4.5  | 7.5          | 0.40           |
| 6020002500 | 25 | Rp 1     | 55         | 90         | 32          | 15         | 4.8  | 11.3         | 0.55           |
| 6020003200 | 32 | Rp 1 1/4 | 70         | 112        | 36          | 17         | 3.5  | 21.7         | 0.89           |
| 6020004000 | 40 | Rp 1 1/2 | 80         | 120        | 46          | 17         | 5    | 28.4         | 1.25           |
| 6020005000 | 50 | Rp 2     | 95         | 150        | 55          | 20         | 4.4  | 47.1         | 1.80           |

### Spare parts

- double screen insert for strainer 602, figure E3120 602 00