




Product Features

- suitable for e.g. figure 160 and figure 193
- incl. EPDM-bonnet gasket
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- check valve with SST spring



Standards and Approvals

- according to accepted materials list from German environmental agency
- for valves acc. DIN 3502 / acc. to DIN EN 13959 provisions

Part no.	for DN	A1	A1	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	H2 (mm)	suitable for figure	kg
E010116001015KP	15	G 1/2		60	26.4	17	115.5	35.5	160, 193 and 137	0.20
E010116001020KP	20	G 3/4		60	32.4	23	119.7	43	160, 193 and 137	0.28
E010116001025KP	25	G 1		70	39.9	29	154	52.5	160, 193 and 137	0.46
E010116001032KP	32	G 1 1/4		70	49.9	37	183.6	63.6	160, 193 and 137	0.54
E010116001040KP	40	G 1 1/2		70	57.9	42	189.6	72.5	160 and 193	0.63
E010116001050KP	50	G 2		90	69.9	54	228	89.6	160 and 193	0.84
E010116000065KP	65	G 1 1/2		120	87.9	67.5	375.4	90	160 and 137	2.09
E010116000080KP	80	G 3		120	101.9	80.5	415.5	99.6	160 and 137	2.59
E010116000100KP	100		M110 x 2	120	120.9	100	332.9	110	160 and 137	3.04