



Product Features

- to avoid heat transmission from drinking water hot (PWH) to drinking water cold (PWC) in mixing taps
- mounting block foamed in pressure and tensile PU hard foam
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- ready to install, suitable for all standard pre-wall elements
- soundproofed
- divisible for different depth gauges
- female pipe thread

Standards and Approvals

- connections in accordance with DVGW W534
- according to accepted materials list from German environmental agency
- to meet the requirements of GEG 2023
- building material class B2 according to DIN 4102
- UBA BWGL Metalle & DVGW W 551-8
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- inside micrometer 150 mm
- pressure rating PN 10
- max. operating temperature 70 °C
- short-term peak temperature 95 °C

Part no.	DN	A1	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	T1 (mm)	T2 (mm)
5500101500	15	Rp 1/2	100	194.5	102	64	153	50	97	264.5	276.5	40	41	75

Part no.	kg
5500101500	1,28