



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- housing with G 2 coaxial thread for meter cartridges
- consisting of VAV maximum flow isolating ball valve and water meter housing with plaster and overflow cap
- for installation of a cold or hot-water metering cartridge
- installation depth variable within the installation dimensions of the water meter
- plastic shaft can be shortened
- female pipe thread
- free from dead spots
- with casted lug for installation with optional base plate
- for use in combination with DN 25 handle set

Standards and Approvals

- valve(s) with DVGW approval
- according to accepted materials list from German environmental agency
- valve(s) with soundproofing certificate according to DIN EN ISO 3822 Class 1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- inside micrometer 153 mm
- pressure rating PN 10
- max. operating temperature 70 °C
- short-term peak temperature 95 °C

Part no.	DN	A1	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	T1 (mm)	kg
8852702000	20	Rp 3/4	110	76	35	296	153	73	16.3	1.54

Accessories

- handle for flush-mounted valves, figure 590 00
- operating cover for flush-mounted valves, figure 591 00
- base plate for stop valve water meter combination CLASSIC for figure 855 27 and figure 885 27, figure 855 00 001
- insulation shell for stop valve water meter combinations CLASSIC VAV, figure 471 17
- cap for stop valve water meter combinations and mounting blocks, figure 855 00 002

Spare parts

- plastic shaft for UP-PLUS flush-mounted valves and UP-PLUS extension set, figure L0100 560 00
- UP-PLUS extension spindle, figure P0100 562 00